

ULTRA SYSTEM PRODUCTS, INC.
12194 S.W. 128TH STREET * MIAMI, FLORIDA 33186
**Manufacturers of Quality Products for
Concrete & Masonry for the New Millennium**
305-255-1464
305-255-5307-FAX
www.ultrasystemproducts.com
e-mail: usp@ultrasystemproducts.com

**APPLICATION SPECIFICATION AND TECHNICAL DATA
FOR
ULTRA MARKING TRAFFIC PAINT
USP-4000
YELLOW, WHITE, BLUE, GREEN**

PRODUCT DESCRIPTION:

Striping Paint is a heavy bodied, latex, marking paint, especially designed for use over bituminous cement and hydraulic cement surfaces, the material is supplied in three standard colors (**white, yellow, blue, green**) The dried film resists weather, water, oil, grease, solvents, and chemicals.

USES:

Recommended for use as a colored surface coating on bituminous and concrete highways, playground, driveways, and parking areas. Principal use includes line markings and striping on parking areas and roadways.

SURFACE PREPARATION:

Asphalt surfaces should be well-cured, clean, free from grease, oil, dirt, and other foreign matter. Flush with water under pressure from a hose and brush vigorously to remove embedded dirt. Grease and oil is best removed by strong detergent cleaning before water flushing. A freshly sealcoated surface should be dry before applying Striping Paint.

APPLICATION:

Thoroughly mix before using. Apply by brush, roller, airless spray or special marking equipment. Striping Paint is applied at the rate of 150 sq. ft. per gallon. A line width of 4 inches will yield approximately 450 lineal feet per gallon, depending on surface texture. If job conditions warrant thinning the material, only water should be used for this purpose.

Apply in good weather. Do not apply in rain or when rain or frost is forecasted within 24 hours. Apply only when the surface and air temperature is 50-F and rising. Keep traffic off of freshly painted surface for a minimum of 4 hours.

CLEAN-UP:

On wet film use clean, cool water. On dried film use toluol solvent.

PHYSICAL PROPERTIES:

| | |
|--------------------------------|--------------------|
| Standard Colors | White, Yellow,Blue |
| Weight Per Gallon, LBS | 11-12.5 Lbs. |
| Solid By Weight | 50-51.7% |
| Solid By Volume | 35.2-39% |
| Recommended Film Thickness ... | 3-4 Mils one coat |
| Dry Time | 30-Min. |

STORAGE AND HANDLING:

KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN

SHELF LIFE:

Approximately twelve months.

SHIPPING WEIGHT (approximately)

5-gallon pail 58 lbs.

CAUTION:

Do not take internally. Close container after each use.

WARNING:

Yellow Striping Paint contains lead. The dried film of this paint may be harmful if eaten or chewed.

Do not apply on toys and other children's articles, furniture, or interior surfaces of any dwelling or facility which may be occupied or used by children.

Do not apply on exterior surfaces of dwelling units, such as windowsills, porches, stairs, or railings, to which children may be commonly exposed.

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either express or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the products. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.