

ULTRA SYSTEM PRODUCTS, INC.
12194 S.W. 128TH STREET * MIAMI, FLORIDA 33186
**Manufacturers of Quality Products for
Concrete and Masonry for the New Millennium.**
305-255-1464
305-255-5307-FAX
www.ultrasystemproducts.com
E-mail: usp@ultrasystemproducts.com

APPLICATION SPECIFICATION AND TECHNICAL DATA

USP-4050 ULTRAPAINT INT/EXT LATEX FLOOR PAINT

DESCRIPTION

USP-4050 Floor Coat is a textured water-based, sand filled acrylic coating specially designed as a skid resistant for exterior light pedestrian traffic, on horizontal use.

FEATURES & BENEFITS

- Water Based
- Decorative Floor Finish
- Slip Resistant
- Environmentally Safe
- May be rolled, brushed, or sprayed
- Ready to be used

USES

USP 4050 Floor Coat can be used on interior / exterior light pedestrian traffic, concrete decks when a skid resistant surface is desired. It can also be used on balconies, pool decks and walkways.

COMPOSITION:

USP-4050 Floor Coat is a water-based high quality acrylic floor coating.

PREPARATION

Clear area and remove all unsound material, oil, grease, paint, dirt, dust, laitance, and any other material that will inhibit the performance of USP 4050 Floor Coat. Repair all non-moving cracks with Flex-Lok (Knife Grade).

COLORS

Ultracoat Floor Coating is available in white and a wide variety of standard and custom colors. (Available upon request)

MIXING

It is very important to mix USP-4050 Floor Coat thoroughly with a mechanical mixer to ensure uniformity.

APPLICATION

USP-4050 Floor Coat may be applied by either roller or brush. Roller nap should be at least $\frac{3}{4}$ " or thicker to ensure a minimum wet thickness of 20 to 28 mils per coat.

CLEAN-UP

All equipment should immediately be cleaned with water before material dries.

COVERAGE

USP 4050 Floor Coat generally covers approximately 55 to 80 square feet per gallon depending on the porosity of the surface.

LIMITATIONS

- Do not apply on vehicular traffic
- Do not apply where subject to ponding water
- Do not apply to frozen surfaces
- Do not add solvents
- Do not apply on unsound concrete surfaces
- Do not apply on concrete that not fully cured
- Do not apply if rain is forecast within 24 hours.

PACKAGING

USP 4050 Floor Coat is available in gallon, 5-gallon pail and 55-gallon drums.

SHELF LIFE

USP-4050 Floor Coat has a shelf life of one year from date of manufacture.

PRECAUTIONS

- Keep out of reach of children
- Harmful if swallowed
- Avoid ingesting
- Wear appropriate eye protection
- Avoid contact with eyes